

入れ子止め テーパータイプ
镶件固定块
 一锥面型一

入れ子止め用スペーサ
镶件固定用垫块

L < 100mm

L > 110mm

型号	材质	硬度
ICS	相当于SKS3	53~56HRC

W | **l₁**

10	
15	7.5
20	
25	10
30	

W | **l₁**

10	
15	10
20	
25	15
30	

W=10 · 15 · 20

L	l ₂
110	32.5
120	35
130	37.5
140	40
150	42.5
160	45
170	47.5
180	50

W=25 · 30

L	l ₂
110	35
120	37.5
130	40
140	42.5
150	45
160	47.5
170	50
180	52.5

d ₁	d ₂	d ₃	t ₁	M	W ₁	型号	W	T	L	A	
						Type			指定单位10mm		
8	4.5	5	5	4	5	ICS (相当于SKS3)	10	15	30~100	1	
								20			
								25*			
								30*			
								35			
11	6.5	7	7	6	6.5		15	20	40~180		3
								25			
								30			
								35			
								40			
14	9	9	9	8	9	20	45	50~180	5		
							50				
							60				
							70				
							80				
					11	25	30				
							35				
							40				
							45				
							50				
						30	60				
							70				
							80				
							90				
							100				

Order 订货范例 型号 - T - L - A
 ICS 15 - 20 - L120 - A5

Delivery 交货期 9 天发货
 上海·广州发货
 数量 > 21时, 请另询交货期。

Example 使用范例 右页

型号	材质	硬度
ICSS	相当于SKS3	53~56HRC

型号	W	T	L	A			
Type			指定单位10mm				
ICSS (相当于SKS3)	5	15	30~100	1			
		20					
		25					
		30					
		35					
		10	10		40	30~180	3
					45		
					50		
					60		
					70		
				80	40~180	5	
				20			
				25			
				30			
				35			
		40					
		45					
		50					
60							
70							
80							

Order 订货范例 型号 - T - L - A
 ICSS 5 - 20 - L100 - A5

Delivery 交货期 9 天发货
 上海·广州发货
 数量 > 21时, 请另询交货期。

Alterations 追加加工 型号 - T - L - A - (MC)
 ICSS 5 - 20 - L100 - A5 - MC

Alteration	Code	Spec.																
	MC	在W尺寸指定侧加工螺纹孔。 <table border="1"> <tr><th>W</th><th>M</th><th>L</th><th>ℓ</th></tr> <tr><td>5</td><td>3</td><td>30~40</td><td>7.5</td></tr> <tr><td>10</td><td>5</td><td>50~100</td><td>10</td></tr> <tr><td></td><td></td><td>110~180</td><td>15</td></tr> </table>	W	M	L	ℓ	5	3	30~40	7.5	10	5	50~100	10			110~180	15
W	M	L	ℓ															
5	3	30~40	7.5															
10	5	50~100	10															
		110~180	15															

Example 使用范例

- ICS: 将螺栓放入拆卸用螺纹孔内。拧入螺栓, 镶件固定块就会逐渐升起出模板。
- ICSS: 使用追加加工MC时, 也可用作镶件固定块。