

C形扣環(軸用) / E形扣環

CAD資料夾名稱: Misc

C形扣環(軸用)

STWN
STWS(不銹鋼)

適用軸

d4: 當扣環嵌入d1時的外圍周最大徑(離隙外徑)

Type	材質	硬度
STWN	彈簧用鋼	44 ~ 53HRC
STWS	SUS304-CSP	36 ~ 44HRC

型式	Type	No.	扣環			參考			適用軸(參考)			NTS單價									
			d3	容許公差	t	b	a	d0	d4	d1	d2	容許公差	m	容許公差	n	1~199 pcs	200 pcs以上				
STWN	STWN	3	2.7	+0.04	0.25	±0.025	0.5	1.7	0.7	7	3	2.85	0	0.35							
		4	3.7	-0.15	0.4	±0.03	0.9	2.2	0.8	9	4	3.8	0	0.5							
		5	4.7		0.6		1.1	2.4	0.8	10.5	5	4.8	-0.04	0.7	+0.10	0.3	19	4	-	-	
		6	5.6	+0.06	0.7	±0.04	1.3	2.8	1	12	6	5.7	0	0.8							
		7	6.5	-0.2	0.8		1.4	3	1	14	7	6.7	0	0.9							
		8	7.4		0.8		1.6	3	1	15	8	7.6	-0.06	0.9							
		9	8.3		0.25	±0.03	0.7	1.4	0.7	9	4	3.7	0	0.3							
		10	9.3		0.4	±0.04	0.7	1.4	0.7	10.5	5	4.7	±0.06	0.45	+0.10	0	1.5	-	-	21	4
		11	10.2		0.65		0.9	2.0	1	14	7	6.5	0	0.7							
		12	11.1		1	±0.05	2.1	3.3	1.5	15	8	7.4	-0.09	0.7							
STWS	STWS(不銹鋼)	13	12		2	3.1	1.2	1.2	18	11	10.5	0	0.7								
		14	12.9		2.1	3.3	1.5	20	13	12.4	0	1.15									
		15	13.8		2.2	3.6	1.7	23	15	14.3	0	-0.11									
		16	14.7		2.2	3.6	1.7	24	16	15.2	0										
		17	15.7		2.2	3.7	1.7	25	17	16.2	0										
		18	16.5		2.6	3.8	1.7	26	18	17	0										
		19	17.5		2.7	3.9	1.8	27	19	18	0										
		20	18.5		2.7	4	1.8	28	20	19	0										
		21	19.5		2.9	4.1	1.8	30	21	20	0										
		22	20.5		2.9	4.2	1.8	31	22	21	0										
STWN	STWN	23	21.4		3.1	4.3	2	32.5	23	22	0										
		24	22.2		3.1	4.3	2	33	24	22.9	0										
		25	23.2		3.1	4.4	2	34	25	23.9	-0.21										
		26	24.2		3.1	4.6	2	35	26	24.9	0										
		28	25.9		3.5	4.7	2	38	28	26.6	0										
		29	26.9		3.5	4.8	2	39	29	27.6	0										
		30	27.9		4	5	2.5	40	30	28.6	0										
		32	29.6		4.5	5.8	2.5	43	32	30.3	0										
		35	32.2		4.8	6.3	2.5	46	35	33	0										
		40	37		5	7.2	2.5	53	40	38	0										
STWS	STWS(不銹鋼)	45	41.5		5.5	7.2	2.5	58	45	42.5	-0.25										
		50	45.8		5.5	7.2	2.5	64	50	47	0										
		52	47.8		5.5	7.2	2.5	66	52	49	0										
		60	55.8		7.4	8.2	2.5	75	60	57	0										
		80	74.5		7.4	8.2	2.5	97	80	76.5	-0.3	2.7	2.5	263	53	709	142				

E形扣環

NETW
NETWS(不銹鋼)

適用軸

Type	材質	硬度	表面處理
NETW	彈簧用鋼	44 ~ 53HRC	鍍三價鉻
NETWS	SUS304	37 ~ 44HRC	-

型式	Type	No.	扣環			適用軸(參考)			NETW·NETWS							
			d	容許公差	D	H	t	容許公差	d1	容許公差	m	容許公差	n	1~199 pcs	200 pcs以上	
NETW	NETW	1.2	1.2		3	±0.1	1	0.3	±0.025	1.4	2	1.2	0.6	15	3	
		1.5	1.5		4		1.3	0	0.4	±0.03	2	2.5	1.5	0.8	15	3
		2	2	-0.09	5		1.7	-0.25	0.4	±0.03	2.5	3.2	2	1	15	3
		2.5	2.5		6		2.1		0.4	±0.03	3.2	4	2.5	1	19	4
		3	3		7		2.6		0.6	±0.04	4	5	3	1	19	4
		4	4		9		3.5		0.6	±0.04	5	7	4	1	19	4
		5	5	0	11		4.3	0	0.6	±0.04	6	8	5	1.2	19	4
		6	6	-0.12	12		5.2	-0.30	0.6	±0.04	7	9	6	1.5	19	4
		7	7		14		6.1		0.8	±0.04	8	11	7	1.8	19	4
		8	8	0	16		6.9	-0.35	0.8	±0.04	9	12	8	2	19	4
9	9	-0.15	18		7.8		0.8	±0.04	10	14	9	2	22	4		

Order 訂購範例

型號: STWS6, NETW9

Delivery 出貨日: 4 日出貨

3 日出貨 僅限當日PM3:30前特別申請之訂單。

C形扣環(孔用) / 彈性銷 / 開口銷

CAD資料夾名稱: Misc

C形扣環(孔用)

RTWN
RTWS(不銹鋼)

適用孔

d4: 當扣環嵌入d1時圓周的最小徑(離隙內徑)

Type	材質	硬度
RTWN	彈簧用鋼	44 ~ 53HRC
RTWS	SUS304-CSP	36 ~ 44HRC

型式	Type	No.	扣環			參考			適用孔(參考)			NTS單價					
			d3	容許公差	t	b	a	d0	d4	d1	d2	容許公差	m	容許公差	n	1~199 pcs	200 pcs以上
RTWN	RTWN	10	10.7		1.5	2.8	1.2	4	10	10.4							
		11	11.8		1.7	3.1	1.5	5	12	12.5							
		12	13	±0.18	1.9	3.6	1.7	6	13	13.6	+0.11	0	1.15			19	5
		13	14.1		1.9	3.6	1.7	7	14	14.6							
		14	15.1		1.9	3.6	1.7	8	15	15.7							
		15	16.2		1.9	3.7	1.7	8	16	16.8							
		16	17.3		1.9	3.8	1.7	9	17	17.8							
		17	18.3		1.9	3.8	1.7	9	17	17.8							
		19	20.5		2.5	4	2	11	19	20	+0.21	0	1.35	+0.14	0	20	6
		20	21.5		2.5	4	2	12	20	21							
RTWS	RTWS(不銹鋼)	21	22.5	±0.2	2.5	4.1	2	12	21	22							
		22	23.5		2.5	4.1	2	13	22	23							
		24	25.9		2.5	4.3	2	15	24	25.2							
		26	27.9		2.5	4.6	2	16	26	27.2							
		28	30.1		3	4.6	2	18	28	29.4							
		30	32.1		3	4.7	2	20	30	31.4							
		32	34.4		3	5.2	2	21	32	33.7							
		37	39.8		3.5	5.2	2	24	37	37	+0.25	0	1.65				
		40	43.5		3.5	5.7	2	28	40	42.5							
		42	45.5		3.5	5.7	2	30	42	44.5							
RTWS	RTWS(不銹鋼)	45	48.5	±0.4	1.75	5.9	2.5	33	45	47.5							
		47	50.5		1.75	6.1	2.5	34	47	49.5							
		52	56.2		1.75	6.5	2.5	39	52	55							
		55	59.2		1.75	6.5	2.5	41	55	58							
		60	64.2		1.75	6.8	2.5	46	60	63	+0.3	0	2.2				
		62	66.2		1.75	6.9	2.5	48	62	65							
		68	72.5		1.75	7.4	2.5	53	68	71							
		72	76.5		1.75	7.4	2.5	57	72	75							
		80	85.5	±0.55	2.5	8	2.5	64	80	83.5							

彈性銷

RNPN
JNPN
JNSPN(不銹鋼)

Type	材質	表面處理
RNPN	SWRH6	鍍三價鉻
JNPN	SWRH6	鍍三價鉻
JNSPN	SUS304	-

型式	Type	No.	d	L	L1	L2	R	h	D1	D2	NTS單價
RNPN	RNPN	6	1.2	25.2	9.7	3.9	3	1.4	6	1.5	19
		8	1.6	33.8	13.1	5.3	4	2.1	8	1.9	25
		10	1.8	40.2	15.7	5.7	5	3	10	2.2	32
		12	2	46	17.5	6	6	4	12	2.4	36

型式	Type	No.	d	d1	L	L1	L2	R	h	S	D1	D2	J
----	------	-----	---	----	---	----	----	---	---	---	----	----	---