

ロケートリング 定位环



盒装销售指南
同一规格批量购买绝对合算!
(但仅限右表规格的产品)
订购方法、交货期、
P.703

规格	型号	D	T	每盒数量
LRBS	60	15	10支	
	100	15	20支	
	100	20	20支	
LRSS	100	25		

定位环装配范例 P.658

RoHS10 LRBS 螺栓型用-2孔-

材质 S45C

RoHS10 LRBF 螺栓型用-4孔-

材质 S45C

RoHS10 LRBD 螺栓型用

材质 S45C

RoHS10 LRJS JIS型用

材质 S45C

RoHS10 LRJST 拉料销压紧型

材质 S45C

RoHS10 LRK 大口径型

材质 S45C

适用螺栓	螺栓孔		t	d	A	型号		
	d2	d1				Type	D	T
M5	5.5	9	5	40	50	LRBS -2孔-	60	10
							15	15
							20	25
			8	70	85		100	10
							15	15
							20	25
M6	6.5	11	3	80	95	LRBF -4孔-	10	10
							15	15
							20	25*
			8	90	105		120	10
							15	15
							20	25
M8	9	14	6	110	130	LRBS -2孔-	150	15
							20	25

*带*符号者仅适用于LRBS。

适用螺栓	螺栓孔		t	R	d	A	型号		
	d2	d1					Type	D	T
M6	6.5	11	9	5	70	85	LRBD	100	15
								20	20
								35	35
								40	40
								45	45
								15	15
			9	5	90	105		120	20
								35	35
								40	40
								45	45
								15	15
								20	20

适用螺栓	螺栓孔		t	A	型号					
	d2	d1			Type	D	T	B		
M6	6.5	11	6.5	85	LRJS	100	15	35	40	50
						20	25	35	40	
						120	15	35	40	50
						20	20	35	40	50
						150	15	40	50	50
						20	20	35	40	50

适用螺栓	螺栓孔		t	A	型号		
	d2	d1			Type	D	T
M6	6.5	11	6.5	85	LRJST	100	15
						20	20

适用螺栓	螺栓孔		D1	d	A	型号	
	d2	d1				Type	D
M6	6.5	11	130	85	115	LRK	100
							150

RoHS10 LRBW 双向定位环-螺栓型用-

材质 S45C

RoHS10 LRSS 带肩型用

材质 S45C

RoHS10 LRSD 带肩型用

材质 S45C

RoHS10 LAR 定位用衬环

材质 S45C

适用螺栓	螺栓孔		d	B	V	D	t	型号	
	d2	d1						Type	No.
M5	5.5	9	40	50	60	100	14	LRBW	100
							16		100-16
							14		120
M6	6.5	11	70	85	100	120	14	LRBW	120-16
							16		130
							14		130-16
							16		130-16

适用螺栓	螺栓孔		t	R	d	A	型号				
	d2	d1					Type	D	T		
M5	5.5	9	4.5	5	40	50	LRSS	60	10		
								15	15		
								20	20		
								25	25		
								10	10		
								15	15		
			8	70	85	10		70	85	100	10
										20	20
										25	25
										30	30
										35	35
										15	15
M6	6.5	11	8	5	80	95	LRSS	110	15		
								20	20		
								25	25		
								30	30		
								35	35		
								15	15		
M8	9	14	6	5	90	105	LRSS	120	15		
								20	20		
								25	25		
								30	30		
								35	35		
								15	15		
M8	9	14	6	10	110	130	LRSS	150	20		
								25	25		

适用螺栓	螺栓孔		t	R	d	A	型号		
	d2	d1					Type	D	T
M6	6.5	11	20	10	70	85	LRSD	100	35
								40	40
								45	45
								120	35
								150	35
								20	45

d	型号		T
	Type	D	
60	LAR	100	10
			15
			20
100	LAR	120	10
			15
			20

Order 订货范例

型号 - T - B

LRBS 120 - 15

LRBW 100 - 15 - 35

LRJS 100 - 15 - 35

Delivery 交货期

•LRBS · LRSS
LRBF · LRJS
LAR · LRJST

库存品

隔日上海·广州发货 P.41
(17:00前订购的库存品可当日发货。)
数量>201时, 请另询交货期。



Example 使用范例

LRBW 双向定位环 -螺栓型用-

LAR 定位用衬环

LRJST 拉料销压紧型

- 正反两个方向均可安装。
- 根据注塑机类型选择定位环外径。
No.=100·120·130时, K=8, H=2
No.=100-16·120-16·130-16时, K=10, H=4

- 在定位环的外侧套入LAR后, 不用更换定位环便可简单对应另一规格。
- 可利用定位环的凸缘压紧各种拉料销。