


规格追加

规格变更

精密级带肩导套  
—油槽型—




红色文字表示 紫色文字表示

规格追加

规格变更

精密级直导套  
—油槽型—



红色文字表示 紫色文字表示

**RoHS10 GBH**

精密级导柱、精密级支撑柱和精密级导套之间配合间隙较小，请在模具温度80℃以下(参考值)使用。( P.784)

材质 SUJ2  
硬度 58HRC~

**RoHS10 GBS**

精密级导柱、精密级支撑柱和精密级导套之间配合间隙较小，请在模具温度80℃以下(参考值)使用。( P.784)

材质 SUJ2  
硬度 58HRC~

d	T	D	H	ℓ																									
				L15	L20	L25	L30	L35	L40	L45	L50	L60	L70	L80	L90	L100	L110	L120											
8	0	12	14	15	15	15	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	
10	-0.005	14	16	15	20	20	20	20	20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
12	-0.005	18	22	15	20	25	25	25	25	25	25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
13	-0.010	20	25	15	20	25	25	25	25	25	25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
16	-0.010	25	30	6	20	25	30	35	30	30	30	30	30	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
20	-0.010	30	35	6	20	25	30	35	40	40	40	40	40	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
25	-0.010	35	40	6	25	30	35	40	45	50	50	50	50	50	50	50	50	50	50	50	50	—	—	—	—	—	—	—	—
28	-0.015	40	45	8	—	—	—	—	—	—	50	56	—	56	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
30	-0.015	42	47	8	—	—	—	—	—	—	50	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60	60
35	-0.015	48	54	8	—	—	—	—	—	—	50	60	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70	70
40	-0.020	55	60	10	—	—	—	—	—	—	50	60	70	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80	80

型号		L															
Type	d	15	20	25	30	35	40	45	50	60	70	80	90	100	110	120	
GBH	8	15	20	25	—	—	—	—	—	—	—	—	—	—	—	—	
	10	15	20	25	30	35	40	—	—	—	—	—	—	—	—	—	
	12	15	20	25	30	35	40	45	50	—	—	—	—	—	—	—	
	13	15	20	25	30	35	40	45	50	—	—	—	—	—	—	—	
	16	20	25	30	35	40	45	50	60	—	—	—	—	—	—	—	
	20	20	25	30	35	40	45	50	60	70	—	—	—	—	—	—	
	25	25	30	35	40	45	50	60	70	80	—	—	—	—	—	—	
	28	50	60	80	—	—	—	—	—	—	—	—	—	—	—	—	
	30	25	30	35	40	45	50	60	70	80	90	100	—	—	—	—	
	35	35	40	50	60	70	80	90	100	110	120	—	—	—	—	—	
40	50	60	70	80	90	100	110	120	—	—	—	—	—	—	—		

Order 订货范例: 型号 GBH 25 - L 60

Delivery 交货期: 隔日上海·广州发货 (17:00前订购的库存品可当日发货。)

库存品: 数量 > 21时, 请另询交货期。

右述以外: d28 · d35 · d40

5 天发货: 数量 > 21时, 请另询交货期。

d	D	T	ℓ																										
			L10	L15	L20	L25	L30	L35	L40	L45	L50	L60	L70	L80	L90	L100													
8	0	12	10	15	15	15	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
10	-0.005	14	10	15	20	20	20	20	20	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
12	-0.005	18	10	15	20	25	25	25	25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
13	-0.010	20	10	15	20	25	25	25	25	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
16	-0.010	25	10	15	20	25	30	35	30	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
20	-0.010	30	—	15	20	25	30	35	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
25	-0.010	35	—	—	20	25	30	35	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
28	-0.015	40	—	—	—	—	—	—	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
30	-0.015	42	—	—	—	—	—	—	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
35	-0.015	48	—	—	—	—	—	—	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—
40	-0.020	55	—	—	—	—	—	—	40	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—	—

型号		L															
Type	d	10	15	20	25	30	35	40	50	60	70	80	90	100			
GBS	8	10	15	20	25	—	—	—	—	—	—	—	—	—			
	10	10	15	20	25	30	35	40	—	—	—	—	—	—			
	12	10	15	20	25	30	35	40	—	—	—	—	—	—			
	13	10	15	20	25	30	35	40	—	—	—	—	—	—			
	16	10	15	20	25	30	35	40	50	—	—	—	—	—			
	20	15	20	25	30	35	40	50	60	70	—	—	—	—			
	25	20	25	30	35	40	50	60	70	—	—	—	—	—			
	28	40	—	—	—	—	—	—	—	—	—	—	—	—			
	30	25	30	35	40	50	60	70	80	—	—	—	—	—			
	35	25	30	35	40	50	60	70	80	90	100	—	—	—			
40	45	50	60	70	80	90	100	—	—	—	—	—	—				

Order 订货范例: 型号 GBS 20 - L 35

右述以外: d28 · d35 · d40

5 天发货: 数量 > 21时, 请另询交货期。

Example 使用范例: 直导套防脱落范例

通常将内六角螺塞拧入导套的防脱槽，以防止导套脱落。与螺塞相对应，在导套的外周开有带状槽。因不直接挤压导套壁厚较薄的部分，所以内径的变形可控制在最小限度。L=10时，使用下表“( )”内的内六角螺塞。

导套内径d	适用内六角螺塞
8 · 10 · 12 · 13 · 16	MSW 6 (4)
20	MSW 6
25 · 28 · 30 · 35 · 40	MSW 8

用内六角螺塞防止导套脱落时，若担心内径变形，可按左图所示，用内六角螺栓的头部压住导套亦可起到较好的效果。请在导柱侧加工螺栓头部大小的沉孔来避空。