



矩形螺旋弹簧

-X-SWF-



Ⓜ有关D尺寸与沉头孔、d尺寸与导销 P.1446

コイルスプリング

螺旋弹簧

Table with columns: D, d, L, Spring constant, F=Lx40%, F=Lx45%, Catalog No., Type D-L. Rows include spring specifications for D=8, 10, 12, 14.

● 负载的计算方法: 负载=弹簧常数×压缩量 (国际单位) N=N/mm×Fmm kgf=kgf/mm×Fmm (kgf=N×0.101972)

Table with columns: D, d, L, Spring constant, F=Lx40%, F=Lx45%, Catalog No., Type D-L. Rows include spring specifications for D=16, 18, 20, 22.

Order and delivery information: Order 订货范例, Delivery 交货期, Price 价格, and contact details for WOS: https://www.misumi-ec.com/cn/ P.57.

Table with columns: D, d, L, Spring constant, F=Lx40%, F=Lx45%, Catalog No., Type D-L. Rows include spring specifications for D=25, 27, 30, 35.

Table with columns: D, d, L, Spring constant, F=Lx40%, F=Lx45%, Catalog No., Type D-L. Rows include spring specifications for D=40, 50, 60.

Ⓜ产品概要 P.1397 Ⓜ矩形螺旋弹簧的使用方法与注意事项 P.1446