



矩形螺旋弹簧

-X-SWL-



有关D尺寸与沉头孔、d尺寸与导销 P.1446

コイルスプリング

螺旋弹簧

D	d	L	弹簧常数		F=L×32%		F=L×36%		Catalog No.		
			N/mm(kgf/mm)	Fmm	Fmm	Fmm	Type	D - L			
8	4	10	10	24.5 (2.50)	3.2	3.6	88 (9.0)	10	X-SWL 8 - 10	15	
			15	16.3 (1.67)	4.8	5.4					20
			20	12.3 (1.25)	6.4	7.2					25
			25	9.8 (1.00)	8.0	9.0					30
			30	8.2 (0.83)	9.6	10.8					35
			35	7.0 (0.71)	11.2	12.6					40
			40	6.1 (0.63)	12.8	14.4					45
			45	5.4 (0.56)	14.4	16.2					50
			50	4.9 (0.50)	16.0	18.0					55
			55	4.5 (0.45)	17.6	19.8					60
			60	4.1 (0.42)	19.2	21.6					65
			65	3.8 (0.38)	20.8	23.4					70
			70	3.5 (0.36)	22.4	25.2					75
			75	3.3 (0.33)	24.0	27.0					80
			80	3.1 (0.31)	25.6	28.8					100

● 负载的计算方法: 负载=弹簧常数×压缩量
(国际单位) N=N/mm×Fmm
kgf=kgf/mm×Fmm
(kgf=N×0.101972)

D	d	L	弹簧常数		F=L×32%		F=L×36%		Catalog No.		
			N/mm(kgf/mm)	Fmm	Fmm	Fmm	Type	D - L			
16	8	20	20	42.9 (4.38)	6.4	7.2	275 (28)	20	X-SWL16 - 20	25	
			25	34.3 (3.50)	8.0	9.0					30
			30	28.6 (2.92)	9.6	10.8					35
			35	24.5 (2.50)	11.2	12.6					40
			40	21.5 (2.19)	12.8	14.4					45
			45	19.1 (1.94)	14.4	16.2					50
			50	17.2 (1.75)	16.0	18.0					55
			55	15.6 (1.59)	17.6	19.8					60
			60	14.3 (1.46)	19.2	21.6					65
			65	13.2 (1.35)	20.8	23.4					70
			70	12.3 (1.25)	22.4	25.2					75
			75	11.4 (1.17)	24.0	27.0					80
			80	10.7 (1.09)	25.6	28.8					90
			90	9.5 (0.97)	28.8	32.4					100
			100	8.6 (0.88)	32.0	36.0					125

Order 订货范例 **X-SWL 22-100**

Delivery 交货期 **库存品**

● 隔日上海·广州发货 (17:00前订购的库存品可当日发货。)

● 数量≥100时, 请另询交货期。

Price 询价联系方式: **WOS: https://www.misumi-ec.com/cn/ P.57**

TEL: 021-6710-8701 / FAX: 021-6710-8984 P.1663

D	d	L	弹簧常数		F=L×32%		F=L×36%		Catalog No.		
			N/mm(kgf/mm)	Fmm	Fmm	Fmm	Type	D - L			
25	12.5	25	25	82.4 (8.40)	8.0	9.0	659 (67)	25	X-SWL25 - 25	30	
			30	68.6 (7.00)	9.6	10.8					35
			35	58.8 (6.00)	11.2	12.6					40
			40	51.5 (5.25)	12.8	14.4					45
			45	45.8 (4.67)	14.4	16.2					50
			50	41.2 (4.20)	16.0	18.0					55
			55	37.4 (3.82)	17.6	19.8					60
			60	34.3 (3.50)	19.2	21.6					65
			65	31.7 (3.23)	20.8	23.4					70
			70	29.4 (3.00)	22.4	25.2					75
			75	27.5 (2.80)	24.0	27.0					80
			80	25.7 (2.63)	25.6	28.8					90
			90	22.9 (2.33)	28.8	32.4					100
			100	20.6 (2.10)	32.0	36.0					125
			125	16.5 (1.68)	40.0	45.0					150

Order 订货范例 **X-SWL 30-100**

Delivery 交货期 **库存品**

● 隔日上海·广州发货 (17:00前订购的库存品可当日发货。)

● 数量≥100时, 请另询交货期。

Price 询价联系方式: **WOS: https://www.misumi-ec.com/cn/ P.57**

TEL: 021-6710-8701 / FAX: 021-6710-8984 P.1663

D	d	L	弹簧常数		F=L×32%		F=L×36%		Catalog No.		
			N/mm(kgf/mm)	Fmm	Fmm	Fmm	Type	D - L			
40	20	40	40	132.0 (13.50)	12.8	14.4	1694 (173)	40	X-SWL40 - 40	45	
			45	118.0 (12.00)	14.4	16.2					50
			50	106.0 (10.80)	16.0	18.0					55
			55	96.2 (9.81)	17.6	19.8					60
			60	88.2 (8.99)	19.2	21.6					65
			65	81.4 (8.30)	20.8	23.4					70
			70	75.6 (7.71)	22.4	25.2					75
			75	70.6 (7.20)	24.0	27.0					80
			80	66.2 (6.75)	25.6	28.8					90
			90	58.8 (6.00)	28.8	32.4					100
			100	52.9 (5.40)	32.0	36.0					125
			125	42.3 (4.32)	40.0	45.0					150
			150	35.3 (3.60)	48.0	54.0					175
			175	30.2 (3.08)	56.0	63.0					200
			200	26.5 (2.70)	64.0	72.0					250

Order 订货范例 **X-SWL 50-100**

Delivery 交货期 **库存品**

● 隔日上海·广州发货 (17:00前订购的库存品可当日发货。)

● 数量≥100时, 请另询交货期。

Price 询价联系方式: **WOS: https://www.misumi-ec.com/cn/ P.57**

TEL: 021-6710-8701 / FAX: 021-6710-8984 P.1663