



ガイドポスト
导柱



無給油ガイドブシュ / フランジ付無給油ガイドブシュ
自润滑导套 / 肩型自润滑导套



■导柱

GPM

※B部: 高频淬火

材质 S45C
硬度 55HRC~
(高频淬火)

| D | D1p6 | D2 | H | E | S | H1 | Catalog No. Type | L |
|-----|------|----|-----|----|----|----|------------------|-----|
| 25 | 25 | 21 | 30 | 8 | 5 | 5 | GPM | 80 |
| | | | | | | | | 100 |
| | | | | | | | | 120 |
| | | | | | | | | 140 |
| | | | | | | | | 160 |
| 30 | 30 | 26 | 40 | 8 | 5 | 5 | GPM | 100 |
| | | | | | | | | 120 |
| | | | | | | | | 140 |
| | | | | | | | | 160 |
| | | | | | | | | 180 |
| 40 | 40 | 36 | 50 | 8 | 5 | 5 | GPM | 200 |
| | | | | | | | | 120 |
| | | | | | | | | 140 |
| | | | | | | | | 160 |
| | | | | | | | | 180 |
| 50 | 50 | 45 | 70 | 10 | 10 | 10 | GPM | 200 |
| | | | | | | | | 160 |
| | | | | | | | | 180 |
| | | | | | | | | 200 |
| | | | | | | | | 250 |
| 60 | 60 | 55 | 90 | 12 | 10 | 10 | GPM | 300 |
| | | | | | | | | 220 |
| | | | | | | | | 250 |
| | | | | | | | | 300 |
| | | | | | | | | 350 |
| 65 | 65 | 60 | 100 | | | | GPM | 250 |
| | | | | | | | | 300 |
| 80 | 80 | 75 | 120 | 12 | 10 | 10 | GPM | 350 |
| | | | | | | | | 400 |
| | | | | | | | | 300 |
| | | | | | | | | 350 |
| 100 | 100 | 95 | 150 | 12 | 10 | 10 | GPM | 400 |
| | | | | | | | | 450 |
| | | | | | | | | 500 |

Order 订货范例 Catalog No. - L
GPM 80 - 300

Delivery 交货期 7 天发货
上海·广州发货
数量≥51时, 请另询交货期。

Price 价格 询价联系方式:
WOS: <https://www.misumi-ec.com/cn/> P.57
TEL: 021-6710-8701 / FAX: 021-6710-8984 P.1663

Alterations 追加加工 Catalog No. - L(LC) - (MC)
GPM 40 - LC110 - MC
11 天发货
上海·广州发货
数量≥101时, 请另询交货期。

| Alterations | Code | Spec. | | | | | | | | | | | | |
|-------------|------|---|---|---|---|----|---|----|-------|----|----|-----|----|----|
| | LC | 变更导柱长度 Lmin. ≤ LC < L 指定单位1mm D ≤ 50适用 | | | | | | | | | | | | |
| | MC | 固定侧部螺纹加工 <table border="1"> <thead> <tr> <th>D</th> <th>M</th> <th>ℓ</th> </tr> </thead> <tbody> <tr> <td>25</td> <td>8</td> <td>18</td> </tr> <tr> <td>30~80</td> <td>12</td> <td>25</td> </tr> <tr> <td>100</td> <td>16</td> <td>32</td> </tr> </tbody> </table> | D | M | ℓ | 25 | 8 | 18 | 30~80 | 12 | 25 | 100 | 16 | 32 |
| D | M | ℓ | | | | | | | | | | | | |
| 25 | 8 | 18 | | | | | | | | | | | | |
| 30~80 | 12 | 25 | | | | | | | | | | | | |
| 100 | 16 | 32 | | | | | | | | | | | | |

■自润滑导套

GBF (铸件型)
GBW (铜合金型)

滑动仅为直线运动。

材质 GBF FC250 石墨(镶嵌)
GBW 高力黄铜 石墨(镶嵌)

| D1 | DH7 | L | h | ℓ | Catalog No. | | |
|-----|---------|-----|-------------|-----|-------------------------|-----|----|
| | | | | | Type | D | |
| 50 | ±0.008 | 30 | +0.021 0 | 50 | GBF (铸件型) GBW (铜合金型) | 30 | |
| 60 | ±0.0095 | 40 | +0.025 0 | 60 | | 40 | |
| 70 | | 50 | 75 | 15 | | 50 | |
| 80 | ±0.011 | 60 | +0.030 0 | 90 | | 20 | 60 |
| 100 | | 80 | 120 | 25 | | 80 | |
| 120 | ±0.013 | 100 | +0.035 0 | 150 | 25 | 100 | |

■肩型自润滑导套

HGBF (铸件型)

材质 FC250 石墨(镶嵌)
附件 内六角螺栓

| D2 | D3 | D1 | DH7 | L | H1 | H2 | a | b | 附件 安装螺栓 | Catalog No. | | |
|-----|-----|-----|---------|-----|-------------|-----|----|------|------------|-------------|---------------|-----|
| | | | | | | | | | | Type | D | |
| 90 | 70 | 50 | ±0.008 | 30 | +0.021 0 | 50 | 20 | 10.8 | 11 | 17.5 | CB10-30 4个 | 30 |
| 100 | 80 | 60 | ±0.0095 | 40 | +0.025 0 | 65 | | | | | | 40 |
| 125 | 100 | 75 | | 50 | 80 | 50 | | | | | | |
| 135 | 110 | 85 | ±0.011 | 60 | +0.030 0 | 100 | | | | | | 60 |
| 170 | 140 | 110 | | 80 | 130 | 80 | | | | | | |
| 190 | 160 | 130 | ±0.0125 | 100 | +0.035 0 | 160 | 25 | 13 | 14 | 20 | CB12-40 4个 | 100 |

Order 订货范例 Catalog No. GBF 50 HGBF 60

Delivery 交货期 库存品 隔日上海·广州发货 P.41 (17:00前订购的库存品可当日发货。)
数量≥51时, 请另询交货期。

Price 价格 询价联系方式:
WOS: <https://www.misumi-ec.com/cn/> P.57
TEL: 021-6710-8701 / FAX: 021-6710-8984 P.1663

自動車型用品
型ガイド部品

汽车模具用
导向零件