

キー溝型凸模用固定キー



廻り止めキー 回转止动键

RoHS10

Catalog No.	M 材质	H 硬度	S 表面处理
PSKB	S45C	45~55HRC	—
PSKBH	SKS3	58~62HRC	铬酸盐光泽处理(银色)

螺栓	D	d	T	Catalog No.	
				Type	No.
M4	10	4.2	3	PSKB	4
			4.5		4-4.5
			5		5-4.5
M5	12	5.2	3	PSKB	5
			4.5		5-4.5
			6		6-4.5
M6	14	6.2	3	PSKB	6
			4.5		6-4.5
			4.5		6-4.5

RoHS10

Catalog No.	M 材质	H 硬度
PSKS	S45C	45~55HRC
PSKJ	SKS3	58~62HRC

螺栓	D	d	t	Catalog No.	
				Type	No.
M4	10	4.5	2.5	PSKS	4
M5	13	5.5	3	PSKS	5
M4	12	4.2	2.5	PSKJ	4
M5	15	5.2	3	PSKJ	5

RoHS10

Catalog No.	M 材质	H 硬度	S 表面处理
PSK	S45C	45~55HRC	—
PSKP	S45C	45~55HRC	—
PSKH	SKS3	58~62HRC	铬酸盐光泽处理(银色)

螺栓	A	B	C	d	T	Catalog No.	
						Type	No.
M4	10	11	6	4.2	3	PSK	4-3
					4.5		4
					5		5-3
M5	11	11	5.5	3	PSK	5	
				4.5		4	
				6		6-3	
M6	12	14	7	3	PSK	6	
				4.5		4-3	
				4.5		4	
M4	11	11	5.5	3	PSKP	5-3	
				4.5		5	
				4.5		6-3	
M5	14	14	7	3	PSKP	6	
				4.5		6	
				4.5		6	
M6	14	14	7	3	PSKH	4-3	
				4.5		4	
				4.5		5-3	
M4	10	11	6	3	PSKH	5	
				4.5		5	
				4.5		6	
M5	12	14	7	3	PSKH	6	
				4.5		6	
				4.5		6	

由于以PSKP为中心位置进行冲孔处理，因此可以不选择方向。

RoHS10

PSKW (长型)

材质 S45C
硬度 45~55HRC

螺栓	B	C	d	P				Catalog No.		T (选择)	A 指定单位1mm	A21~30	A31~40	A41~50	A51~60
				A=21~30	A=31~40	A=41~50	A=51~60	Type	No.						
M4	11	6	4.2	10	20	30	—	PSKW	4	3	21~50	○	○	○	—
M5			5.2	—	20	30	40		5	4.5	31~60	—	○	○	○

Order 订货范例: Catalog No. — T — A

Delivery 交货期: 库存品

Example 使用范例: PSKB 4, PSKS 5, PSKP 5, PSKH 4 — 3 — 40

长型 仅PSKW: 7天发货

Example 使用范例: 固定键, PSKW

RoHS10

KE

材质 S45C
硬度 45~55HRC

Catalog No.	
Type	L
KE	8
	10
	12
	15
	20
	25
30	

Order 订货范例: Catalog No. KE 12

Delivery 交货期: 库存品

隔日上海·广州发货 (17:00前订购的库存品可当日发货。)

数量≥201时，请另询交货期。

Example 使用范例: 回转止动键

RoHS10

KED, KES, KEG

L	公差
10	0 -0.15
15	0 -0.18
20 · 25 · 30	0 -0.21
35 · 40 · 45 · 50	0 -0.25
55 · 60 · 70 · 80	0 -0.30
90 · 100 · 110	0 -0.35

JIS B 1301—1996

Type	材质
KED	S45C
KES	
KEG	

拉深强度 600N/mm²以上

B _{h9}	H公差	C	Catalog No.		L
			Type	B	
2	0	2	KED KES KEG	2	10 15 20
3	-0.025	3		3	10 15 20 25 30
4	0	4		4	10 15 20 25 30 35 40 45 50
5	-0.030	5		5	10 15 20 25 30 35 40 45 50
6	0	6		6	10 15 20 25 30 35 40 45 50 55 60
7	-0.036	7		7	15 20 25 30 35 40 45 50 55 60
8	0	8		8	15 20 25 30 35 40 45 50 55 60 70 80
10	-0.043	10		10	15 20 25 30 35 40 45 50 55 60 70 80
12	0	12		12	20 25 30 35 40 45 50 55 60 70 80
14	-0.090	14		14	30 35 40 45 50 55 60 70 80 90
15	0	15		15	30 35 40 45 50 55 60 70 80 90
16	-0.110	16		16	40 45 50 55 60 70 80 90 100
18	0	18		18	40 45 50 55 60 70 80 90 100 110

Order 订货范例: Catalog No. — L

Delivery 交货期: 库存品

隔日上海·广州发货 (17:00前订购的库存品可当日发货。)

数量≥201时，请另询交货期。

B=2~12: 11天发货

B=14~18: 11天发货

Alterations 追加加工: Catalog No. — L(LC)

11天发货

Alteration	Code	Spec.
全长追加加工	LC	LC=指定单位1mm
		B LC范围
		2 5~20
		3 6~30
		4 8~50
		5 8~50
		6 10~60
		7 15~80
		8 15~80
		10 15~80
		12 20~80
		14 25~90
		16 35~100
18 35~110		